

Frequency:

Frequency range: 0~ 18 GHz

VSWR: 1.5 Max. under 6GHz

Insertion Loss (dB): 0.177 under 6GHz

PN
index

Cable Type	Dimensions		
	A	B	C
RG402	3.70	4.70	1.00
RG405	2.30	3.20	0.60

0

1

Electrical:

Impedance: 50 ohm

Voltage Rating: ≥ 500 V rms (Depending on cable)

Insulator Resistance : ≥ 5 G Ω

Dielectric Withstanding Voltage : ≥ 750 V rms

Contact Resistance : Center Contact ≤ 3 m Ω .

Outer Contact ≤ 2.5 m Ω



Mechanical:

Mating : 1/4-36 UNS Screw-on Coupling

Recommended Mating Torque : 7.1~9.7lbs

Coupling Nut Retention Force : ≥ 60.7 lbs

Environmental:

Temperature Range : -65 $^{\circ}$ C to 165 $^{\circ}$ C

Corrosion (Salt Spray) : MIL-STD-202,

Method 101, Cond.B

Thermal Shock : MIL-STD-202, Method 107, Cond.B

Mechanical : MIL-STD-202, Method 213, Cond.I

Vibration : MIL-STD-202, Method 204, Cond.D



Notes:

1- The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.

2- Any changes for interface dimensions are strictly prohibited.

3- The Material and plating are in various options per customer's request.

4- A complete information for connectors is available upon request.

Tolerances	Scale	Abbr.	Rev.	Part Number	F111-134x PN index above	 
.X ± 0.2 .XX ± 0.1 .XXX ± 0.05	NTS	ST	B			
PAGE	All Dimensions in mm (Unless Otherwise Specified)					
1 of 1						