

Frequency:

Frequency range: 0 to 11 GHz (50Ω)
0 to 1 GHz (75Ω)

VSWR: ≤1.3 (straight connector)
≤ 1.35 (right angle connector)

Insertion Loss (dB): 0.177 under 6GHz (50 ohm)
0.177 under 1GHz (75 ohm)

Electrical:

Impedance: 50/75 ohm

Voltage Rating: ≥500 V rms (Depending on cable)

Insulator Resistance : ≥ 5 GΩ

Dielectric Withstanding Voltage : 1500 V rms

Contact Resistance : Center Contact ≤ 1.5 mΩ

Outer Contact ≤ 1 mΩ

Mechanical:

Mating : 7/16 - 28UNEF Screw-on Coupling

Recommended Mating Torque: 4.1 lbs ~ 6.1 lbs

Coupling Nut Retention Force: ≥101.2 lbs

Cable Retention Force: ≥ 12.1 lbs (for RG316)

≥ 28.7 lbs (for RG58)

≥ 38.3 lbs (for RG59)



Environmental:

Temperature Range : -55°C to 155°C

Corrosion (Salt Spray) : MIL-STD-202,

Method 101, Cond.B

Vibration : MIL-STD-202, Method 204, Cond.B

Thermal Shock : MIL-STD-202, Method 107, Cond.B

Mechanical : MIL-STD-202, Method 213, Cond.G

Notes:

1- The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.

2- Any changes for interface dimensions are strictly prohibited.

3- The Material and plating are in various options per customer's request.

4- A complete information for connectors is available upon request.


PN
index
0

Type	Dimensions						
	A	B	C	D	a	b	c
H1	0.94	1.52	12.7	19.1	1.02	1.78	12.7

Tolerances
.X ±0.2
.XX ±0.1
.XXX ±0.05

Scale	Abbr.	Rev.
NTS	ST	B

Part Number **F142-129X**
PN index above



PAGE
1 of 1

All Dimensions in mm
(Unless Otherwise Specified)

Date

2021/08/24

