

Frequency:

Frequency range: 50 ohm: 0~ 2 GHz

VSWR: 1.5 Max. under 1GHz

Insertion Loss (dB): 0.177 under 1GHz

PN
index

Cable Type	Dimensions			
	A	B	C	D
0 RG178	1.6	2.8	4.8	3.2
1 RG174,316	3.1	4.5	5.1	2.9
2 1.32	1.05	2.7	4.3	1.45
3 1.13	1.05	2.7	4.3	1.3
4 0.81	1.4	2.7	4.3	0.9

Mechanical:

Mating : M8 x 0.75 Threaded Coupling

Recommended Mating Torque : 0.6 lbs ~ 2.5 lbs

Coupling Nut Retention Force : ≥ 101.2 lbs





Notes:

1- The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.

2- Any changes for interface dimensions are strictly prohibited.

3- The Material and plating are in various options per customer's request.

4- A complete information for connectors is available upon request.

Tolerances	Scale	Abbr.	Rev.	Part Number	 
.X ± 0.2 .XX ± 0.1 .XXX ± 0.05	NTS	ST	B		
PAGE 1 of 1	All Dimensions in mm (Unless Otherwise Specified)			Date 2021/09/07	