



Frequency:

Frequency range: 50 ohm: 0~ 2 GHz

VSWR: 1.5 Max. under 1GHz

Insertion Loss (dB): 0.177 under 1GHz


PN index	Cable Type	Dimensions			
		A	B	C	D
0	RG174,316	1.8	2.8	0.6	3.2
1	RG58	3.2	4.6	1.0	5.6
2	RG223,400	3.2	4.6	1.0	5.8
3	RG6	5.1	6.4	1.2	7.5
4	H155	4.2	5.5	1.6	6.5

Mechanical:

Mating : M8 x 0.75 Threaded Coupling

Recommended Mating Torque : 0.6 lbs ~ 2.5 lbs

Coupling Nut Retention Force : ≥ 101.2 lbs




Notes:

1- The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.

2- Any changes for interface dimensions are strictly prohibited.

3- The Material and plating are in various options per customer's request.

4- A complete information for connectors is available upon request.

Tolerances	Scale	Abbr.	Rev.	Part Number	
.X ±0.2 .XX ±0.1 .XXX ±0.05	NTS	ST	B		
PAGE 1 of 1	All Dimensions in mm (Unless Otherwise Specified)			Date 2021/09/07	