



Frequency:

Frequency range: 0~ 6 GHz

VSWR: ≤ 1.15 @ DC to 4 GHz
 ≤ 1.40 @ 4 to 6 GHz

Insertion Loss (dB): 0.177 under 6 GHz

Electrical:

Impedance: 50 ohm

Voltage Rating: ≤ 170 V rms (Depending on cable)

Insulator Resistance : ≥ 1 G Ω

Dielectric Withstanding Voltage : 500 V rms

Contact Resistance : Center Contact ≤ 10 m Ω .

Outer Contact ≤ 5 m Ω

Mechanical:

Mating : Snap-on Coupling

Engagement Force : ≤ 3.4 lbs

Disengagement Force : 1.4 lbs ~ 3.4 lbs

Cable Retention Force: ≥ 7.3 lbs (for RG178)

≥ 12.1 lbs (for RG316)



Environmental:

Temperature Range : -55°C to 155°C

Corrosion (Salt Spray) : MIL-STD-202,

Method 101, Cond.B

Vibration : MIL-STD-202, Method 204, Cond.C

Thermal Shock : MIL-STD-202, Method 107, Cond.F

Mechanical : MIL-STD-202, Method 213, Cond.B

Notes:

1- The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.

2- Any changes for interface dimensions are strictly prohibited.

3- The Material and plating are in various options per customer's request.

4- A complete information for connectors is available upon request.

PN index	Type	Dimensions				
		A	B	C	a	b
0	N0	0.7	3.0	3.4	1.0	3.0
1	A1	0.7	3.0	3.45	1.0	3.0

Tolerances .X ± 0.2 .XX ± 0.1 .XXX ± 0.05	Scale NTS	Abbr. ST	Rev. B	Part Number F172-132X <small>.....</small> PN index above	
PAGE 1 of 1	All Dimensions in mm (Unless Otherwise Specified)			Date 2021/08/25	