



## Frequency:

Frequency range: 0~18 GHz

VSWR: 1.5 Max. under 6GHz

Insertion Loss (dB): 0.177 under 6GHz

## Electrical:

Impedance: 50 ohm

Voltage Rating:  $\geq 500$  V rms (Depending on cable)

Insulator Resistance :  $\geq 5$  G $\Omega$

Dielectric Withstanding Voltage : 1000 V rms

Contact Resistance : Center Contact  $\leq 3$  m $\Omega$ .

Outer Contact  $\leq 2.5$  m $\Omega$

PN  
index

Type	Dimensions					
	A	B	C	D	b	c
<b>L0(1.0)</b>	0.5	1.02	5.33	1.0	1.20	5.33
<b>L0(1.22)</b>	0.5	1.02	5.33	1.22	1.20	5.33
<b>L0(1.35)</b>	0.5	1.02	5.33	1.35	1.20	5.33
<b>L0(1.6)</b>	0.5	1.02	5.33	1.6	1.20	5.33
<b>L0(1.75)</b>	0.5	1.02	5.33	1.75	1.20	5.33

## Mechanical:

Mating : 1/4-46 UNS Screw-on Coupling

Recommended Mating Torque : 7.1~9.7lbs

Coupling Nut Retention Force :  $\geq 60.7$  lbs



## Environmental:

Temperature Range : -65°C to 165°C

Corrosion (Salt Spray) : MIL-STD-202,

Method 101, Cond.B

Thermal Shock : MIL-STD-202, Method 107, Cond.B

Mechanical : MIL-STD-202, Method 213, Cond.I

Vibration : MIL-STD-202, Method 204, Cond.D

## Notes:

1- The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.

2- Any changes for interface dimensions are strictly prohibited.

3- The Material and plating are in various options per customer's request.

4- A complete information for connectors is available upon request.

Tolerances	Scale	Abbr.	Rev.	Part Number	
.X $\pm 0.2$ .XX $\pm 0.1$ .XXX $\pm 0.05$	NTS	ST	B		
PAGE <b>1 of 1</b>	All Dimensions in mm (Unless Otherwise Specified)			Date 2021/09/06	