





APPLICATIONS and Usage	Product FEATURES
<ul style="list-style-type: none"> • Test Equipment • Radar & Electronic Warfare • Communication systems 	<ul style="list-style-type: none"> • Small Structure, Low Cost, Drop-In Type • Wideband Frequency Range, High Reliability • Field Removable SMA(F) Available <p>Low Conversion Loss</p> <p>Low LO Drive Power</p>

ELECTRICAL SPECIFICATIONS @25°C:

Parameter	Min	Typical	Max	Units
INPUT PARAMETERS				
RF Frequency Range	0.01		3	GHz
RF input VSWR		2.5:1		Ratio
LO frequency Range	0.01		3	GHz
LO Power Range	7		13	dBm
LO VSWR		3:1		Ratio
TRANSFER CHARACTERISTICS				
Conversion Loss		8		dB
Single-sideband noise figure		8		dB
LO-to-RF isolation		25		dB
LO-to-IF isolation		25		dB
RF-to-IF isolation		25		dB
Input power at 1 dB compression		+5		dBm
Input two-tone third-order intercept point		19		dBm
OUTPUT PARAMETERS				
output IF frequency	0.01		0.5	MHz
output IF VSWR		2.5:1		Ratio

All Features is customizable Based on Customer Request	Part Number: IIRM-000130	
PAGE 1 of 2	Date 2021/09/11	


ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Operating Temperature	-40		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Air bone		

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Case type	30*25*12	Max	Millimeter
Weight	50	Max	gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-F		
Impedance	50		ohms

OUTLINE DRAWING (mm):



All Features is customizable Based on Customer Request

Part Number: **IIRM-000130**

