



## Design Features :

- \* Can be dual junction even three for high isolation.
- \* High RF performance, ultra-competitive price.
- \* Military, space and commercial applications.
- \* Custom design available upon request.

Freq.Range (GHz)	Insertion LossMax(dB)	IsolationMin(dB)	VSWRMax	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)	PN INDEX
8.0 ~ 18.0	0.8	16	1.5	60	60	SMA-M to SMA-F	-40 ~ +75	00
8.0 ~ 18.0	0.8	16	1.5	60	60	SMA-F	-40 ~ +75	01

- ✧ List are specified frequency range and other ranges available.
- ✧ Please enter the below information when inquiry and mark \* is a must.

1. The specific frequency ranges
2. Power handling (Forward, Reverse, Peak, etc.)
3. Connect type (SMA Male/ Female, N Male/ Female, etc.)
4. Other special requests if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

<b>Tolerances</b> .X ±0.2 .XX ±0.1 .XXX ±0.05	Scale	Abbr.	Rev.	<b>Part Number:</b> CCX-111 PN index above	
	NTS	ST	B		
PAGE	All Dimensions in mm (Unless Otherwise Specified)			Date	
<b>1 of 1</b>				2021/08/08	